

Click on links in red for further details

* Stated airflows are at nominal voltage against zero static pressure

New Products

Description	Series
High Airflow Low Power Consumption 92x32mm DC Axial Fans	San Ace 92 G-Type
Slim Type Active Heat Sink for Intel®Pentium® 4 μPGA478 1.8-2.2 GHz	San Ace MC
High Performance Active Heat Sink for Intel®Pentium® 4 μPGA478 2.2 GHz	San Ace MC
Spiral Copper Active Heat Sink for Intel®Pentium® 4 PGA423 & μPGA478 2.2 GHz	San Ace MC-HX
19" Rack Mountable Ø172 x 147 x 25mm DC Axial Fans	Dyna Ace
High Airflow 119x38mm Long Life Fans	San Ace 120L G-Type
1U Compatible Active Heat Sink for Intel®Pentium® III FC-PGA2 1.4GHz	San Ace MC
High Airflow Low Power Consumption 119x25mm & 119x38mm DC Axial Fans	San Ace 120 G-Type

DC Axial Fans

Edge Length (mm)	Thickness (mm)	Voltage (V)	Air Flow (cfm)	Series
40	10, 15, 20, 28	5, 12, 24	3.18 - 14.8	Fine Ace
52	15	5, 12, 24	7.24 - 13.3	Micro Ace
60	15, 20, 25	5, 12, 24, 48	7.40 - 37.0	Pico Ace
80	15, 20, 25, 32	5, 12, 24, 48	14.8 - 55.0	Petit Ace
92	25, 32	12, 24, 48	28.3 - 71.7	Mini Ace
	32	12, 24, 48	42.4 - 88.3	NEW San Ace 92 G-Type
119	25, 38	5, 12, 24, 48	43.1 - 102.4	San Ace
	25, 38	12, 24, 48	58.0 - 137.0	NEW San Ace 120 G-Type
127	38	12, 24, 48	132.0 - 170.0	San Ace 127
140	38	12, 24, 48	116.0 - 159.0	San Ace 140
Ø172	51, 150x51, ^{NEW} 147x25	12, 24, 48	108.0 - 279.0	Dyna Ace
Ø200	70	24, 48	290.0 - 369.0	San Ace 200

Splash Proof Fans

Edge Length (mm)	Thickness (mm)	Voltage (V)	Air Flow (cfm)	Series
80	25	12, 24, 48	22.3 - 39.2	Splash Proof Fan W-Type
92	25	12, 24, 48	28.2 - 48.8	
119	38	12, 24, 48	79.0 - 106.0	
140	38, 51	12, 24, 48	116.5 - 208.3	
80	25	12, 24	23.0 - 33.2	Splash Proof Fan WS-Type
92	25	12, 24	28.2 - 48.7	
119	38	12, 24, 48	77.7 - 102.4	

Click on links in red for further details

* Stated airflows are at nominal voltage against zero static pressure

Long Life Fans

Edge Length (mm)	Thickness (mm)	Voltage (V)	Air Flow (cfm)	Series
60	25	12, 24, 48	12.7 - 27.6	Long Life Fan
80	25	12, 24, 48	22.2 - 42.4	
92	25	12, 24, 48	28.2 - 58.0	
119	38	5, 12, 21, 24, 48	54.8 - 106.0	
140	38, 51	12, 24, 48	116.5 - 208.3	
Ø172	51, 150x51	12, 24, 48	148.3 - 226.0	Long Life Fan (Low Noise) NEW San Ace 120L G Type
119	38	12, 24, 48	77.7 - 102.4	
119	38	12, 24, 48	74.0 - 138.0	

DC Centrifugal Blowers

Edge Length (mm)	Thickness (mm)	Voltage (V)	Air Flow (cfm)	Series
76	30	12, 24	12.7 - 27.6	Scirocco Ace
119	32	12, 24	18.2 - 27.5	
127	32	12, 24	21.5 - 32.0	
160	40	12, 24	44.5 - 57.2	

CPU Active Heatsinks

CPU	Core Speed (MHz)	Series
Intel® Pentium®4 µPGA478/PGA423	up to 2200	San Ace MC NEW San Ace MC-HX
Intel® Pentium®III FC-PGA2/FC-PGA	500 - 1400	
Intel® Pentium®II SECC2	733 - 1000	
Intel® Celeron™ FC-PGA2/FC-PGA/PPGA	300 - 1300	
Intel® Pentium®Pro	All	
Intel® Pentium®	All	
Mobile CPU, PCI Card	All	
Intel® Pentium®4 µPGA478/PGA423	up to 2200	

Celeron™, Pentium®, Pentium®II, Pentium®III, Pentium®4 are registered trademarks of Intel Corporation.

San Cooler

Edge Length (mm)	Thickness (mm)	Voltage (V)	Air Flow (cfm)	Series
60	25	12, 24	12.7 - 27.6	San Cooler
80	25	12, 24	23.0 - 53.0	
92	25	12, 24	23.0 - 62.1	